



# **MAXX RIPPER®**

# **THE ULTIMATE GROUNDBREAKER!**



**TRUE GROUNDBREAKING PERFORMANCE -  
TACKLE SOIL COMPACTION AND MAXIMISE YIELDS**



## **ASK OUR EXPERTS**

**FIND  
OUT  
MORE**



[www.k-line.net.au](http://www.k-line.net.au)

**SAFETY NEVER HURTS!™**

Always read the Operators Manual before operating any equipment. Inspect equipment before using it and be sure it is operating properly. Follow the product safety signs and use any safety features provided. CNH Australia reserves the right to make improvements in design and changes in specifications at any time without notice and without incurring any obligation to install them on units previously sold. Specifications, descriptions, and illustrative material are as accurate as known at time of publication but are subject to change without notice. Availability of some models and equipment builds varies.

© Copyright 2025 CNH America LLC. All Rights Reserved. K-Line Ag and CNH Capital are registered trademarks of CNH America LLC. - We have updated our information notice about privacy ("Privacy Statement") to give you the latest information on how we collect and use your personal data. You can review our updated Privacy Statement by clicking the privacy link on the footer.

# MAXXRIPPER®

Manufactured for breaking hard pans and deep tillage application, this machine has deep ripping tynes to break up compacted soils to a depth of approx. 600mm (23").

Where soil compaction is encountered, the MaxxRipper® is your answer for:

- Superior root structure
- Greater nutrient uptake
- Better moisture availability
- Healthier plant development
- Higher yields

## MaxxRipper® Features

- Extremely robust frame
- Heavy duty deep-ripping shanks with shear pin system
- Heavy duty knifing roller for soil conditioning and clod busting
- V-pattern shank layout for greater efficiency: gives lighter draft and better tracking ability
- Huge main frame members 250 x 150mm
- Shank spacing – 500-550mm
- Optional range of shanks, points and guard styles available
- Underframe clearance 780mm
- 7, 9 & 11 shank models available

## Point Options

### Minimum Soil Disturbance Point



Standard on all machines. Ideal for breaking that hard pan with minimal soil disturbance.

### Cast Wing Point



Ideal for soil mixing and inversion.

## MAXXRIPPER® SPECIFICATIONS

CODE	DESCRIPTION	OPERATING WIDTH APPROX.	TRACTOR POWER RANGE (hp)	WEIGHT APPROX.	TRANSPORT HEIGHT APPROX.	TRANSPORT WIDTH APPROX.	TRANSPORT LENGTH
3235T	7 Shank Ripper, Trailing	3.5m 11.5'	280-420 hp	4,500 kg 9,922.5 lb	2.1m 6.9'	3.8m 12.4'	6.95m 22.8'
3245T	9 Shank Ripper, Trailing	4.5m 14.8'	360-500 hp	5,000 kg 11,025 lb	2.1m 6.9'	4.9m 16.0'	7.32m 24.0'
3260T	11 Shank Ripper, Trailing	6.0m 19.7'	450-600 hp	5,500 kg 12,127.5 lb	2.1m 6.9'	6.0m 19.6'	7.70m 25.3'