

THUNDERRIPPER®

HEAVY-DUTY COMPACT RIPPER FOR SOIL IMPROVEMENT



WITH TINES REACHING IDEAL DEPTHS, THE THUNDERRIPPER® IMPROVES PLANT GROWTH, NUTRIENT AND MOISTURE ABSORPTION.



ASK OUR EXPERTS

FIND OUT MORE



www.k-line.net.au

SAFETY NEVER HURTS!

Always read the Operators Manual before operating any equipment. Inspect equipment before using it and be sure it is operating properly. Follow the product safety signs and use any safety features provided. CNH Australia reserves the right to make improvements in design and changes in specifications at any time without notice and without incurring any obligation to install them on units previously sold. Specifications, descriptions, and illustrative material are as accurate as known at time of multiplican but are subject to change without notice. Availability of some models and equipment builds varies

© Copyright 2025 CNH America LLC. All Rights Reserved. K-Line Ag and CNH Capital are registered trademarks of CNH America LLC. – We have updated our information notice about privacy "Privacy Statement") to give you the latest information on how we collect and use your personal data. You can review our updated Privacy Statement by clicking the privacy link on the footer

THUNDERRIPPER®



The ThunderRipper® by K-Line Ag is a heavy-duty yet compact ripper designed to break up compacted soils and improve root penetration. With tines capable of reaching a depth of approximately 450-500mm, the ThunderRipper® promotes better plant development by facilitating the entry of nutrients and moisture, as well as enhancing the accumulation of organic materials in the soil.

The K-Line Ag ThunderRipper® offers a range of features that make it an ideal solution for addressing common challenges in modern farming operations. Its robust construction includes heavy-duty main frame members, ensuring durability and strength.

Additionally, the ripper is equipped with heavy-duty tines and an adjustable knifing roller, allowing for efficient one-pass soil conditioning. The ThunderRipper® is available in multiple configurations, including 3 Point Linkage, and Trailing Folding models, with operating widths ranging from 2.5 to 6 meters.

Benefits

- Improved root penetration
- Enhanced nutrient and moisture entry
- Versatility to suit various operations
- Robust and durable construction
- Easy transportation

THUNDERRIPPER® SPECIFICATIONS

Model	Description	Operating Width	Transport Width	НР	No. Tines	Tine Spacing Range
3425D	3PL, Rigid	2.5m	2.7m	200-400	5-7	500m & 360mm
3435D	3PL, Rigid	3.5m	3.7m	280-440	7-11	500mm & 325mm
3445D	3PL, Rigid	4.5m	4.9m	330-440	9-13	500mm & 350mm
3445P	Trailing, Folding*	4.5m	3.2m	360-440	9-11	410mm & 500mm
3460D	3PL, Rigid	6m	6.2m	385-440	11-13	550mm & 460mm
3460P	Trailing, Folding*	6m	3.5m	385-440	11-13	550mm & 460mm

^{*}Hydraulic Trip Shanks (Paxton Plow) are available on 4.5m & 6m Forward Folding models.

